Flux Coated Cadium-Free Silver Brazing Rod

EutecRod 1028 FC



- Usefull for parts with no uniform clearance
- No preparatory fluxing necessary
- Recommended for brazing stainless steel, nickel or nickel alloys where stress cracking occures during the heating process
- Suitable for brazing thin sections or thin cracks
- Good corrosion resistance



DESCRIPTION:

EutecRod 1028FC is a low-temperature, Cadmium-free, silver brazing alloy for joining most ferrous and non-ferrous metals. Its lower melting temp makes it an ideal candidate for replacing Cadmium-bearing alloys in a variety of thinwalled joint, including applications where FDA approval is necessary.

TECHNICAL DATA:

Solidus: 1145°F (618°C) Liquidus: 1205°F (651°C)

Brazing Range: 1205°F - 1400°F (651°C - 760°C)

Electrical Conductivity: 11.9 % IACS

Electrical Resistivity: 14.5 Michrohm-cm For Joint Clearances: .001 to .005 inches

Max. Operating Temp.: 400°F (204°C) continuous service

600°F (315°C) intermittent service

AVAILABILITY

Available in 18" lengths in 3/64", 1/16" and 3/32" diameters. Packaged in 0.5 lb., 1 lb., 2 lb. and 5.5 lb. packs.

WELDING PARAMETERS:

Preparation: The base metal surfaces to be brazed must be clean and free of all dirt, oil, grease and oxides such as rust.

Finishing: All the corrosive flux residue must be removed after brazing. Rinse with water while the parts are still warm, or rinse with hot water.

TYPICAL APPLICATIONS:

Suitable for brazing thin sections of fabricated steel boxes, butt joints, fixtures, brass wave guides, brass/copper radiator repair, heat exchangers (thin cracks) and valves

YOUR RESOURCE FOR PROTECTION, REPAIR AND JOINING SOLUTIONS



EUTECTIC CORPORATIONN94 W14355 Garwin Mace Drive

Menomonee Falls, WI 53051 USA Tel.: +1 (800) 558-8524 eutectic.com **EUTECTIC CANADA**

428, rue Aimé-Vincent Vaudreuil-Dorion, Québec J7V 5V5 Canada Tel.: +1 (800) 361-9439 eutertic ca



^{*}International Annealed Copper Standard

^{**}Resistance based on uniform Length and Cross-section