High Quality Electrode for Welding Gray Cast Irons When Strength and Machinabilty are Required

EutecTrode[®] 3055





- Excellent crack resistance
- Good for thick or variable section castings
- Machines cleanly with no smearing
- Better mechanical properties than conventional cast iron rods



DESCRIPTION:

Eutectic 3055 is recommended for welding engineeringgrade cast iron when mechanical properties similar to the base metal are required.

Eutectic 3055 deposits high-strength weld metal with excellent crack resistivity properties on thick-section casting. Ease of welding in all positions gives high welder appeal.

TYPICAL APPLICATIONS:

- Pump and Differential Housings
- Motor Blocks
- High Phosphorus Irons and Steels
- Heavy Section Casting Repair
- Dimensional Restoration

TECHNICAL DATA:


Current: DCEP (electrode +) Typical Tensile Strength: 55,000 psi (380 N/mm²) Hardness: HRB 90

Diameter	3/32" (2.4mm)	1/8" (3.2mm)
Amperage	110-120	130-140


WELDING PARAMETERS:

Preparation: Clean joint and/or parts to be welding thoroughly. Terminate crack growth by drilling ¼" holes at the leading points. Preheat casting to 150-200°C, holding for 1 hour per inch of thickness. Prepare joint with Eutectic ChamferTrode[®] or ExoTrode[®] with either a single-V or double V, depending on joint thickness and accessibility. Allow a root opening of 1/8" for full penetration welds.

Technique: Deposit short runs no longer than 2-in. and moderately peen 2nd and subsequent passes. For long cracks in heavy castings use either a cascade and/or block deposition sequence.



Cascade Sequence: Weld metal is deposited in overlapping layers.



Block Sequence: Weld metal is deposited in intervening increments.

Post-welding: Slow cool after welding using available insulating material such as vermiculite, sand or fire retardant blankets.

YOUR RESOURCE FOR PROTECTION, REPAIR AND JOINING SOLUTIONS



EUTECTIC CORPORATION N94 W14355 Garwin Mace Drive Menomonee Falls, WI 53051 USA Tel.: +1 (800) 558-8524 eutectic.com EUTECTIC CANADA 428, rue Aimé-Vincent Vaudreuil-Dorion, Québec J7V 5V5 Canada Tel.: +1 (800) 361-9439 eutectic.ca



Statement of Liability: Due to variations inherent in specific applications, the technical information contained herein, including any information as to suggested product applications or results, is presented without representation or warranty, expressed or implied. Without limitation, there are no warranties of merchantability or of fitness for a particular purpose. Each process and application must be fully evaluated by the user in all respects, including suitability, compliance with applicable law and non-infringement of the rights of others, and Eutectic Corporation and its affiliates shall have no liability in respect thereof. 3055 05/19 © 2008, Eutectic Corporation, ® Reg. T.M., Printed in the U.S.A.