General Purpose Hardfacing Electrodefor Abrasion and Impact

EutecTrode 5002



- Easy and complete slag removal
- Crack-resistant deposits
- Excellent for field repairs
- Welder-friendly



DESCRIPTION:

EutecTrode 5002 is a general purpose hardfacing electrode for resistance to abrasion and impact. It is suitable for the surfacing of new or worn machine components used for earthmoving or rock crushing.

TECHNICAL DATA:

Typical Hardness (single pass): 54-58 HRC Polarity: AC/DC (+)

Positions: Flat and Horizontal

Recommended Amperages

Dia	1/8" (3.2mm)	5/32" (4.0mm)	3/16" (5.0mm)
Amps	100-140	140-180	180-230

TYPICAL APPLICATIONS:

Shredders

APPLICATIONS INDUSTRIES

Feed Screws Pulp and Paper

Recycling

Bucket Teeth Mining
Crushers Quarry

WELDING PARAMETERS:

Preparation: Clean the weld area and remove scale and oxide. For parts below 40°F or over 1" thick, preheat to 150°F. Higher carbon steels require higher preheat (300°F - 500°F). Do not preheat Hadfield manganese steel castings above 200°F.

Technique: Maintain a medium to short arc. The electrode should be inclined at a 15-30° angle in the direction of travel. Weld using stringer beads or 2x weaving. Be advised that weaving more than 2x the electrode diameter is not advised as it may overheat the base metal and degrade weld deposit wear properties. Prior to extinguishing the arc, back whip the craters to reduce crater cracking.

Post-welding: Slow cool parts in still air. High carbon steels and air hardenable steels should be covered with a heat retardant blanket.

YOUR RESOURCE FOR PROTECTION, REPAIR AND JOINING SOLUTIONS



EUTECTIC CORPORATION

N94 W14355 Garwin Mace Drive Menomonee Falls, WI 53051 USA Tel.: +1 (800) 558-8524 eutectic.com

EUTECTIC CANADA

428, rue Aimé-Vincent Vaudreuil-Dorion, Québec J7V 5V5 Canada Tel.:+1 (800) 361-9439 eutectic.ca

