



# **EuTronic Arc Spray EAS1-i**

Twin Wire Arc Spray Technology




- Lightweight and slim design inverter energizer
- Computerised controlled circuit & intuitive software
- Reliable Push Pull system for spraying up to 20m in all positions
- Quick and easy switching between closed loop and open loop spraying
- Air-cooled contact tubes with wear-resistant tips
- Double grooved feed rollers for double operation life
- Extremely portable with a user-friendly control panel

## Why EuTronic Arc Spray EAS1-i.

EuTronic Arc is the highest productivity thermal spraying process. EuTronic Arc is an Arc Spray Process using a pair of wires which are melted by an electric arc.

This molten material is atomized by compressed gas and propelled toward the workpiece to form a coating. EuTronic Arc is a cold spray process having the advantage of not requiring the use of oxygen, kerosene or a combustible gas which means more economical coatings. Low running costs, high spray rates and efficiency make it a good tool for spraying extensive areas or a large number of parts.



Contact tubes with screw tip design



Improved compact yet powerful drive unit

### EuTronic Arc


As the electrically conductive wires are fed toward each other, a short circuit is established between the wires creating an arc with a temperature of around 5000°C.

This heat causes the wire tips to melt. Compressed gas – most often air – is used to atomize the molten tips and propel the droplets towards the substrate at velocities exceeding 100 meters per second. This combination of high temperature and particle velocities gives arc-sprayed coatings superior bond strengths and low porosity levels at high spray rates. Furthermore, this Twin Wire Arc Spray technology is a “cold process” as the substrate temperature can be kept low during spraying avoiding metallurgical changes and distortion within the workpiece.

The Gun design has been upgraded with screw-in tips for ease of replacement and redesigned air concentrator together with a front wire guide gives significant efficiency gains.

**Plus the following benefits compared with painting, zinc galvanizing or chromium plating:**

- EuTronic Arc provides a lot of benefits compared with conventional welding processes used for wear protection:**
- Most substrate types can be coated.
  - No thermal distortion or metallurgical alteration of the substrate.
  - Low pre-heating requirements.
  - Low heat input during spraying.
  - No heat treatment after coating.
  - No dilution of the coating.
  - Fastest coating speeds.
  - Better control over deposit thickness reducing machining time and saving materials.
- Sprayed zinc or aluminum is used as primer bond layers for paints.
  - No advantage of paints over adequately sealed, sprayed metal coatings
  - More robust than paints to withstand rougher handling and service.
  - Sacrificial action, particularly of sprayed zinc, prevents corrosion from edges of the damaged sprayed coating.
  - Immediate corrosion protection with sprayed corrosion-resistant wires.
  - Infinite shelf life if properly stored
  - No effluent disposal problems
  - No size limit for parts to be treated
  - On-site coating possible
  - Variation of coating thickness from area to area to provide extra protection
  - Used to restore corrosion protection on damaged areas of welded galvanized steel.



Schematic diagram

## EuTronic Arc Spray EAS1-i system

## Optional

The EAS1-i was developed to improve running costs, coating deposition and ease of maintenance. The Arc Gun and the drive system are coupled to a 350 A power source. This power source features sealed electronics for excellent reliability in the harshest of spray environments. The wire feeder unit is neatly mounted on the power source. There is no motor in the gun. Instead, the Gun uses a patented 'Synchrodrive' system, where a single, sealed motor with a flexible drive arrangement, powers a reliable, positive drive push / pull up to a distance of 20 m. Graduated / quantifiable tensioner for the wire.

- Sealed 350 A power source for reliability.
- 1.6mm wires standard. From 2.0mm to 2.5mm optional.
- Air-cooled cables for low weight.
- Excellent gun manoeuvrability.
- 5 m supplies package standard. Optional 10 m, 20 m.
- Easy to maintain for lower downtime costs.
- Wire spool, coil and drum feeder option capabilities.
- Doublegrooved feed rollers can be reversed for improved wear life.
- Standard input voltage 380 V or 460 V or 575 V.



**Arcjet:** The ArcJet fits on the gun to inject air in front of the nozzle. The ArcJet constricts the spray pattern thus reducing overspray and allowing more confined areas such as deep slots, to be sprayed. Therefore significant improvements in deposit efficiency can be made especially on small-diameter components.

**Arc spray extension neck:** The arc spray extension neck enables improved access to awkward areas such as deep bores with a minimum diameter of 75 mm and rear sides of welded stiffeners etc. The extension neck allows for spraying either straight ahead or at an angle and for applications using power up to 200 amps. It is available in 3 different lengths 500, 1000 and 1500 mm.



### Proficiency in arc spray applications with EuTronic Arc Wires:

EuTronic Arc Wires are unique, specially formulated for Arc Spraying to provide the industry with wear and corrosion protection solutions. The EuTronic Arc Spray EAS1-i is designed to spray solid and cored wires for many different applications with outstanding results. Spray rates from 8 to 36kg/hr can be achieved depending on the sprayed alloy.

#### Optional Models:

3 variants to suit your chosen country:



EUTRONIC  
1-I-CE.



EUTRONIC  
1-I-460V.



EUTRONIC  
1-I-575V.

#### Typical applications:

- Anti-wear coatings.
- Bridges (concrete and steel).
- Cement works.
- Engineering bond coats.
- Mining.
- Offshore/oil & gas.
- Pulp and paper.
- Steel works.
- Shipbuilding/ marine.
- Structural steelwork.
- Thermal power plants.
- Vessels and enclosures.
- Waste and recycling.
- Wind turbine towers, fences.

**Supplies packages:** The supplies packages consisting of cables and conduits are available in different lengths 5, 10 and 20 meters.



Power, Air and  
Control Cables



Flexible Drive Cable



Wire Conduits

**Remote control:** The 5 meters remote control allows a remote operation of the EuTronic Arc Spray 4 system with a robust design for use on semi-automatic installations. The remote control buttons and switch mimic those of the Gun.



Castolin Eutectic application specialists working in the field are never far away. The secret of our success is our close cooperation and partnership with customers.

The TeroLink database makes documented solutions for applications accessible. Together we can analyze your individual requirements and develop cost-effective, tailor-made solutions.

Let us advise you.



*Pioneering  
Industrial  
Sustainability*

# **EuTronic Arc Spray EAS1-i**



*Your resource for protection, repair and joining solutions*

Statement of Liability: Due to variations inherent in specific applications, the technical information contained herein, including any information as to suggested product applications or results, is presented without representation or warranty, expressed or implied. Without limitation, there are no warranties of merchantability or of fitness for a particular purpose. Each process and application must be fully evaluated by the user in all respects, including suitability, compliance with applicable law and non-infringement of the rights of others, and Castolin Eutectic and its affiliates shall have no liability in respect thereof.

[www.castolin.com](http://www.castolin.com)

[www.eutectic.com](http://www.eutectic.com)